


27260 Type

.3 to 1.2pF



27270 Type

.6 to 4.5pF

GIGA-TRIM® CAPACITORS

JMC P/N MIL SPEC	RANGE pF	TC PPM/°C	MIN. Q @ 250 MHz	DIMENSIONS (INCHES)
27261SL PC22J1R2	.3 to 1.2 >5 TURNS	0 ± 50	5000	
27261 PC21J1R2	.3 to 1.2 >5 TURNS	0 ± 50	5000	
27263 PC23J1R2	.3 to 1.2 >5 TURNS	0 ± 50	5000	
27264 PC23J1R2	.3 to 1.2 >5 TURNS	0 ± 50	5000	

GIGA-TRIM® CAPACITORS

JMC P/N MIL SPEC	RANGE pF	TC PPM/°C	MIN. Q @ 250 MHz	DIMENSIONS (INCHES)
27271SL PC22J4R5	.6 to 4.5 >8 TURNS	0 ± 50	3000	
27271 PC21J4R5	.6 to 4.5 >8 TURNS	0 ± 50	3000	
27273 PC24J4R5	.6 to 4.5 >8 TURNS	0 ± 50	3000	
27274 PC23J4R5	.6 to 4.5 >8 TURNS	0 ± 50	3000	