



Features/Benefits

- Ratings up to 10 AMPS
- Snap-in panel and PC mounting
- Actuators with screwdriver slot
- Quick connect terminals available
- RoHS compliant

Specifications

- » CONTACT RATING: 10.1 AMPS @ 125 V AC; 4 AMPS @ 28 V DC; 5 AMPS @ 250 V AC (UL/CSA). 2.0 (0.5) AMPS @ 250 V AC, T85 (VDE).
- » ELECTRICAL LIFE: 10,000 make-and-break cycles at full load.
- » CONTACT RESISTANCE: Below 10 mΩ typ. initial @ 2-4 V DC, 100 mA.
- » INSULATION RESISTANCE: 10^9 Ω min.
- » DIELECTRIC STRENGTH: 1,000 Vrms min. @ sea level.
- » OPERATING TEMPERATURE: -30°C to +85°C.

Typical Applications

- Appliances

Materials

- » HOUSING: 6/6 nylon (UL94V-2), black.
- » TOP PLATE: 6/6 nylon (UL94V-2), black.
- » ACTUATOR: Glass filled polyester (UL94V-0), '01 and 02' styles, black (standard); '12, 13 and 14' styles, red (standard).
- » CONTACTS: Copper, silver plated.
- » TERMINALS: Copper, silver plated.
- » CONTACT SPRING: Music wire or stainless steel.
- » TERMINAL SEAL: Epoxy.